AMENDMENTS TO THE CLAIMS

As indicated below, Applicant is amending Claims 1, 14, 15, 22 and 24 and is cancelling Claims 13 and 23 without prejudice or disclaimer. Claims 2–12, 16–21 and 25–40 remain as originally filed.

1.   (Currently Amended)   A method of performing data string operations comprising:

routing a series of instructions to a general purpose microprocessor having a first execution unit for executing instructions;

analyzing said series of instructions so as to detect an instruction to perform a data string operation;

routing said instruction to perform a data string operation to a second execution unit separate from said first execution unit, wherein said second execution unit receives an undecoded version of said instruction;

controlling read and write operations to and from external memory with said first execution unit ~~general purpose microprocessor~~ via control circuitry and without intervention by said second execution unit, wherein said external memory is external to said general purpose microprocessor; and

controlling read and write operations to and from external memory with said second execution unit via said control circuitry and without intervention by said first execution unit.

2.   (Original) The method of Claim 1, wherein said first execution unit is on a first integrated circuit and wherein said second execution unit is on a second integrated circuit.

3.   (Original) The method of Claim 2, wherein said second integrated circuit includes a bus interface unit in association with said second execution unit.

4.   (Original) The method of Claim 2, wherein said second integrated circuit comprises a memory controller.

5.   (Original) The method of Claim 4, wherein said act of routing said data string instruction to said memory controller comprises writing said data string instruction to an I/O address.

6.   (Original) The method of Claim 5, wherein said I/O address is normally not used for I/O devices.

7.   (Original) The method of Claim 1, additionally comprising checking the content of a data cache to determine if at least a portion of a data string which is the subject of said data string instruction is present in said data cache.

8.   (Original) The method of Claim 7, wherein modified cache lines present in said data cache which contain data forming at least a portion of said data string are written back to main memory before or during the execution of said data string instruction.

9.   (Original) A digital processing system optimized for string manipulations comprising:

an instruction fetch unit coupled to an external memory;

a first execution unit coupled to receive, decode, and perform assembly language arithmetic and logic instructions received from memory via said instruction fetch unit;

a second execution unit coupled to receive, decode, and perform assembly language string manipulation instructions received from memory via said instruction fetch unit; and

memory circuitry, external to said first and second execution units, configured to be alternatively controlled by said first execution unit and said second execution unit using the same memory control circuitry, wherein said first execution unit and said second execution unit are separately coupled to said memory control circuitry.

10.   (Original) The digital processing system of Claim 9 additionally comprising a data cache, wherein said data cache stores a subset of that data which is stored in said memory, and wherein said second execution unit is coupled to said data cache and configured to maintain data cache coherency with said memory.

11.   (Original) The digital processing system of Claim 10, additionally comprising a plurality of comparators having a first input coupled to said data cache and a second input coupled to a source of compare data.

12. (Original) The digital processing system of Claim 11, wherein said source of compare data comprises said second execution unit.

13. (Cancelled)

14. (Currently Amended) A processing system comprising:

an instruction fetch unit coupled to an external memory;

a first execution unit ~~coupled~~ configured to receive, decode, and perform assembly language arithmetic and logic instructions received from memory via said instruction fetch unit;

a second execution unit ~~coupled~~ configured to receive, decode, and perform assembly language string manipulation instructions received from memory via said instruction fetch unit;

memory circuitry, external to said first and second execution units; and

a bus interface unit, coupled to said memory circuitry, said first execution unit, and said second execution unit, wherein said memory circuitry is configured to be alternatively controlled by said first execution unit and said second execution unit via said bus interface unit, wherein said first execution unit is configured to operate said memory circuitry independently of said second execution unit, and wherein said second execution unit is configured to operate said memory circuitry independently of said first execution unit.

15. (Currently Amended) A method of performing data string operations comprising:

routing a series of individual assembly language opcodes to a general purpose microprocessor having a first execution unit for executing instructions;

analyzing said series of assembly language opcodes so as to detect an instruction to perform a data string operation;

routing said instruction to perform a data string operation to a second execution unit separate from said first execution unit, wherein said instruction comprises at least one individual opcode for performing a data string operation, and wherein said second execution unit receives an undecoded version of said instruction;

controlling read and write operations to and from memory external to said general purpose microprocessor with said first execution unit ~~general purpose microprocessor~~ via control circuitry and independent of said second execution unit; and

controlling read and write operations to and from said memory with said second execution unit via said control circuitry and independent of said first execution unit.

16.   (Original) The method of Claim 15, wherein said first execution unit is on a first integrated circuit and wherein said second execution unit is on a second integrated circuit.

17.   (Original) The method of Claim 16, wherein said second integrated circuit comprises a memory controller.

18.   (Original) The method of Claim 17, wherein routing said instruction to perform a data string operation to said second execution unit comprises writing said data string instruction to an I/O address.

19.   (Original) The method of Claim 18, wherein said I/O address is normally not used for I/O devices.

20.   (Original) The method of Claim 15, additionally comprising checking the content of a data cache to determine if at least a portion of a data string which is the subject of said data string instruction is present in said data cache.

21.   (Original) The method of Claim 20, wherein modified cache lines present in said data cache which contain data forming at least a portion of said data string are written back to main memory before or during the execution of said data string instruction.

22.   (Currently Amended) A processing system comprising:

a host processing integrated circuit;

a ~~separate~~ memory integrated circuit;

a ~~separate~~ memory controller integrated circuit coupled between said host processing integrated circuit and said memory integrated circuit; and

dedicated string execution circuitry integral to said memory controller integrated circuit and configured to perform string manipulation instructions on data in said memory integrated circuit without intervention by said host processing integrated circuit, and wherein said host processing circuit is configured to operate said memory controller independently of said string execution circuitry.

23.   (Cancelled)

24.   (Currently Amended)   A method of performing data string operations comprising:

routing a series of instructions to a general purpose microprocessor having a first execution unit for executing instructions on data independent of a second execution unit;

analyzing said series of instructions with said first execution unit so as to detect an instruction to perform a data string operation on said data; and

routing with the first execution unit said instruction to perform a data string operation to a second execution unit separate from said first execution unit, wherein said second execution unit receives an undecoded version of said instruction.

25.   (Original) The method of Claim 24, wherein said first execution unit is on a first integrated circuit and wherein said second execution unit is on a second integrated circuit.

26.   (Original) The method of Claim 25, wherein said second integrated circuit includes a bus interface unit in association with said second execution unit.

27.   (Original) The method of Claim 25, wherein said second integrated circuit comprises a memory controller.

28.   (Original) The method of Claim 27, wherein said act of routing said data string instruction to said memory controller comprises writing said data string instruction to an I/O address.

29.   (Original) The method of Claim 28, wherein said I/O address is normally not used for I/O devices.

30. (Original) The method of Claim 26, additionally comprising checking the content of a data cache to determine if at least a portion of a data string which is the subject of said data string instruction is present in said data cache.

31. (Original) The method of Claim 30, wherein modified cache lines present in said data cache which contain data forming at least a portion of said data string are written back to main memory before or during the execution of said data string instruction.

32. (Original) A method of performing data string operations comprising:

routing a series of instructions to a general purpose microprocessor having a first execution unit;

analyzing said series of instructions so as to detect an instruction to perform a data string operation; and

routing said instruction to perform a data string operation to a second execution unit such that said first execution unit does not receive said instruction.

33. (Original) The method of Claim 32, wherein said first execution unit is on a first integrated circuit and wherein said second execution unit is on a second integrated circuit.

34. (Original) The method of Claim 33, wherein said second integrated circuit includes a bus interface unit in association with said second execution unit.

35. (Original) The method of Claim 33, wherein said second integrated circuit comprises a memory controller.

36. (Original) The method of Claim 35, wherein said act of routing said data string instruction to said memory controller comprises writing said data string instruction to an I/O address.

37. (Original) The method of Claim 36, wherein said I/O address is normally not used for I/O devices.

38. (Original) The method of Claim 32, additionally comprising checking the content of a data cache to determine if at least a portion of a data string which is the subject of said data string instruction is present in said data cache.

39.   (Original) The method of Claim 38, wherein modified cache lines present in said data cache which contain data forming at least a portion of said data string are written back to main memory before or during the execution of said data string instruction.

40.   (Original) The method of Claim 32, wherein analyzing said series of instructions is performed by an instruction fetch unit.